

# Linux-Foundation


## Exam Questions CKAD

Certified Kubernetes Application Developer (CKAD) Program



**NEW QUESTION 1**

Exhibit:



Task:

Update the Deployment app-1 in the frontend namespace to use the existing ServiceAccount app.

- A. Mastered
- B. Not Mastered

**Answer: A**

**Explanation:**

Solution:

Text Description automatically generated

```

File Edit View Terminal Tabs Help
The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.


Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.

candidate@node-1:~$ vi ~/spicy-pikachu/backend-deployment.yaml
candidate@node-1:~$ kubectl config use-context sk8s
Switched to context "sk8s".
candidate@node-1:~$ vim .vimrc
candidate@node-1:~$ vim ~/spicy-pikachu/backend-deployment.yaml
candidate@node-1:~$ kubectl apply -f ~/spicy-pikachu/backend-deployment.yaml
deployment.apps/backend-deployment configured
candidate@node-1:~$ kubectl get pods -n staging
NAME                                READY   STATUS    RESTARTS   AGE
backend-deployment-59d449b99d-cxct6 1/1     Running   0           20s
backend-deployment-59d449b99d-h2zjq 0/1     Running   0           9s
backend-deployment-78976f74f5-b8c85 1/1     Running   0           6h40m
backend-deployment-78976f74f5-flfsj 1/1     Running   0           6h40m
candidate@node-1:~$ kubectl get deploy -n staging
NAME                READY   UP-TO-DATE   AVAILABLE   AGE
backend-deployment 3/3     3             3           6h40m
candidate@node-1:~$ kubectl get deploy -n staging
NAME                READY   UP-TO-DATE   AVAILABLE   AGE
backend-deployment 3/3     3             3           6h41m
candidate@node-1:~$ vim ~/spicy-pikachu/backend-deployment.yaml
candidate@node-1:~$ kubectl config use-context k8s
Switched to context "k8s".
candidate@node-1:~$ kubectl set serviceaccount deploy app-1 app -n frontend
deployment.apps/app-1 serviceaccount updated
candidate@node-1:~$

```

**NEW QUESTION 2**

Exhibit:



Task:

Create a Deployment named expose in the existing ckad00014 namespace running 6 replicas of a Pod. Specify a single container using the ifccncf/nginx: 1.13.7 image

Add an environment variable named NGINX\_PORT with the value 8001 to the container then expose port 8001

- A. Mastered
- B. Not Mastered

**Answer: A**

**Explanation:**

Solution:

```
candidate@node-1:~$ kubectl config use-context k8s
Switched to context "k8s".
candidate@node-1:~$ kubectl create deploy expose -n ckad00014 --image lfccncf/nginx:1.13.7 --dry-run=client -o yaml > dep.yaml
candidate@node-1:~$
```

Text Description automatically generated

```
File Edit View Terminal Tabs Help
apiVersion: apps/v1
kind: Deployment
metadata:
  creationTimestamp: null
  labels:
    app: expose
  name: expose
  namespace: ckad00014
spec:
  replicas: 6
  selector:
    matchLabels:
      app: expose
  strategy: {}
  template:
    metadata:
      creationTimestamp: null
      labels:
        app: expose
    spec:
      containers:
      - image: lfccncf/nginx:1.13.7
        name: nginx
        ports:
        - containerPort: 8001
        env:
        - name: NGINX_PORT
          value: "8001"
```

Text Description automatically generated

```
candidate@node-1:~$ kubectl config use-context k8s
Switched to context "k8s".
candidate@node-1:~$ kubectl create deploy expose -n ckad00014 --image lfccncf/nginx:1.13.7 --dry-run=client -o yaml > dep.yaml
candidate@node-1:~$
candidate@node-1:~$ vim dep.yaml
candidate@node-1:~$ kubectl create -f dep.yaml
deployment.apps/expose created
candidate@node-1:~$ kubectl get pods -n ckad00014
NAME                                READY   STATUS    RESTARTS   AGE
expose-85dd99d4d9-25675             0/1     ContainerCreating   0           6s
expose-85dd99d4d9-4fhcc             0/1     ContainerCreating   0           6s
expose-85dd99d4d9-fl7j              0/1     ContainerCreating   0           6s
expose-85dd99d4d9-tt6rm             0/1     ContainerCreating   0           6s
expose-85dd99d4d9-vjd8b             0/1     ContainerCreating   0           6s
expose-85dd99d4d9-vtzpq            0/1     ContainerCreating   0           6s
candidate@node-1:~$ kubectl get deploy -n ckad00014
NAME    READY   UP-TO-DATE   AVAILABLE   AGE
expose  6/6     6            6           15s
candidate@node-1:~$
```

**NEW QUESTION 3**

Exhibit:



Context

A web application requires a specific version of redis to be used as a cache. Task

Create a pod with the following characteristics, and leave it running when complete:


- The pod must run in the web namespace. The namespace has already been created
- The name of the pod should be cache
- Use the lfcncf/redis image with the 3.2 tag
- Expose port 6379

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Solution:



**NEW QUESTION 4**

Exhibit:



Context

You are tasked to create a secret and consume the secret in a pod using environment variables as follow:

Task

- Create a secret named another-secret with a key/value pair; key1/value4
- Start an nginx pod named nginx-secret using container image nginx, and add an environment variable exposing the value of the secret key key 1, using COOL\_VARIABLE as the name for the environment variable inside the pod

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:


Solution:






**NEW QUESTION 5**

Exhibit:



Task:

Update the Pod ckad00018-newpod in the ckad00018 namespace to use a NetworkPolicy allowing the Pod to send and receive traffic only to and from the pods web and db



- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Solution:

```
candidate@node-1:~$ kubectl config use-context nk8s
Switched to context "nk8s".
candidate@node-1:~$ kubectl describe netpol -n ckad00018
```

```

Name:          all-access
Namespace:     ckad00018
Created on:    2022-09-24 04:27:37 +0000 UTC
Labels:       <none>
Annotations:  <none>
Spec:
  PodSelector:  all-access=true
  Allowing ingress traffic:
    To Port: <any> (traffic allowed to all ports)
    From: <any> (traffic not restricted by source)
  Allowing egress traffic:
    To Port: <any> (traffic allowed to all ports)
    To: <any> (traffic not restricted by destination)
  Policy Types: Ingress, Egress

Name:          default-deny
Namespace:     ckad00018
Created on:    2022-09-24 04:27:37 +0000 UTC
Labels:       <none>
Annotations:  <none>
Spec:
  PodSelector:  <none> (Allowing the specific traffic to all pods in this namespace)
  Allowing ingress traffic:
    <none> (Selected pods are isolated for ingress connectivity)
  Not affecting egress traffic
  Policy Types: Ingress
candidate@node-1:~$ kubectl label pod ckad00018-newpod -n ckad00018 web-access=true
pod/ckad00018-newpod labeled
candidate@node-1:~$ kubectl label pod ckad00018-newpod -n ckad00018 db-access=true
pod/ckad00018-newpod labeled
candidate@node-1:~$
```

**NEW QUESTION 6**

Exhibit:



Context

Your application's namespace requires a specific service account to be used.

Task


Update the app-a deployment in the production namespace to run as the restrictedservice service account. The service account has already been created.

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Solution:



### NEW QUESTION 7

Exhibit:



Context

A container within the poller pod is hard-coded to connect the nginxsvc service on port 90. As this port changes to 5050 an additional container needs to be added to the poller pod which adapts the container to connect to this new port. This should be realized as an ambassador container within the pod.

Task

- Update the nginxsvc service to serve on port 5050.
- Add an HAProxy container named haproxy bound to port 90 to the poller pod and deploy the enhanced pod. Use the image haproxy and inject the configuration located at /opt/KDMC00101/haproxy.cfg, with a ConfigMap named haproxy-config, mounted into the container so that haproxy.cfg is available at /usr/local/etc/haproxy/haproxy.cfg. Ensure that you update the args of the poller container to connect to localhost instead of nginxsvc so that the connection is correctly proxied to the new service endpoint. You must not modify the port of the endpoint in poller's args . The spec file used to create the initial poller pod is available in /opt/KDMC00101/poller.yaml

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Solution:

apiVersion: apps/v1 kind: Deployment metadata:

name: my-nginx spec:

selector:

matchLabels: run: my-nginx replicas: 2 template: metadata: labels:

run: my-nginx spec: containers:

- name: my-nginx image: nginx ports:

- containerPort: 90

This makes it accessible from any node in your cluster. Check the nodes the Pod is running on: `kubectl apply -f ./run-my-nginx.yaml`

`kubectl get pods -l run=my-nginx -o wide`

NAME READY STATUS RESTARTS AGE IP NODE

my-nginx-3800858182-jr4a2 1/1 Running 0 13s 10.244.3.4 kubernetes-minion-905m my-nginx-3800858182-kna2y 1/1 Running 0 13s 10.244.2.5 kubernetes-

minion-ljyd Check your pods' IPs:

`kubectl get pods -l run=my-nginx -o yaml | grep podIP` podIP: 10.244.3.4

podIP: 10.244.2.5

**NEW QUESTION 8**

Exhibit:



Context

Developers occasionally need to submit pods that run periodically. Task

Follow the steps below to create a pod that will start at a predetermined time and]which runs to completion only once each time it is started:


- Create a YAML formatted Kubernetes manifest /opt/KDPD00301/periodic.yaml that runs the following shell command: date in a single busybox container. The command should run every minute and must complete within 22 seconds or be terminated by Kubernetes. The Cronjob name and container name should both be hello
- Create the resource in the above manifest and verify that the job executes successfully at least once

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Solution:



```

Readme Web Terminal THE LINUX FOUNDATION
apiVersion: batch/v1beta1
kind: CronJob
metadata:
  name: hello
spec:
  jobTemplate:
    metadata:
      name: hello
    spec:
      template:
        spec:
          containers:
            - image: busybox
              name: hello
              args: ["/bin/sh", "-c", "date"]
              restartPolicy: Never
  schedule: '*/* * * * *'
  startingDeadlineSeconds: 22
  concurrencyPolicy: Allow

```


```

Readme Web Terminal THE LINUX FOUNDATION
student@node-1:~$ kubectl create cronjob hello --image=busybox --schedule "* * * * *" --dry-run=
client -o yaml > /opt/KDPD00301/periodic.yaml
error: unable to match a printer suitable for the output format "yaml", allowed formats are: go-t
emplate, go-template-file, json, jsonpath, jsonpath-as-json, jsonpath-file, name, template, templatefile
, yaml
student@node-1:~$ kubectl create cronjob hello --image=busybox --schedule "* * * * *" --dry-run=
client -o yaml > /opt/KDPD00301/periodic.yaml
student@node-1:~$ vim /opt/KDPD00301/periodic.yaml
student@node-1:~$ kubectl create -f /opt/KDPD00301/periodic.yaml
cronjob.batch/hello created
student@node-1:~$ kubectl get cronjob
NAME          SCHEDULE          SUSPEND   ACTIVE   LAST SCHEDULE   AGE
hello        */1 * * * *      False    0        <none>          6s
student@node-1:~$

```

**NEW QUESTION 9**

Exhibit:



Task:

A pod within the Deployment named buffalo-deployment and in namespace gorilla is logging errors.

1) Look at the logs identify errors messages.

Find errors, including User "system:serviceaccount:gorilla:default" cannot list resource "deployment" [...] in the namespace "gorilla"

The buffalo-deployment 'S manifest can be found at -/prompt/escargot/buffalo-deployment.yaml

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Solution:

Text Description automatically generated

```

File Edit View Terminal Tabs Help
deployment.apps/backend-deployment configured
candidate@node-1:~$ kubectl get pods -n staging
NAME                                READY   STATUS    RESTARTS   AGE
backend-deployment-59d449b99d-cxct6  1/1     Running   0           20s
backend-deployment-59d449b99d-h2zjq  0/1     Running   0           9s
backend-deployment-78976f74f5-b8c85  1/1     Running   0           6h40m
backend-deployment-78976f74f5-flfsj  1/1     Running   0           6h40m
candidate@node-1:~$ kubectl get deploy -n staging
NAME            READY   UP-TO-DATE   AVAILABLE   AGE
backend-deployment  3/3     3             3           6h40m
candidate@node-1:~$ kubectl get deploy -n staging
NAME            READY   UP-TO-DATE   AVAILABLE   AGE
backend-deployment  3/3     3             3           6h41m
candidate@node-1:~$ vim ~/spicy-pikachu/backend-deployment.yaml
candidate@node-1:~$ kubectl config use-context k8s
Switched to context "k8s".
candidate@node-1:~$ kubectl set serviceaccount deploy app-1 app -n frontend
deployment.apps/app-1 serviceaccount updated
candidate@node-1:~$ kubectl config use-context k8s
Switched to context "k8s".
candidate@node-1:~$ vim ~/prompt-escargot/buffalo-deployment.yaml
candidate@node-1:~$ vim ~/prompt-escargot/buffalo-deployment.yaml
candidate@node-1:~$ kubectl apply -f ~/prompt-escargot/buffalo-deployment.yaml
deployment.apps/buffalo-deployment configured
candidate@node-1:~$ kubectl get pods -n gorilla
NAME                                READY   STATUS    RESTARTS   AGE
buffalo-deployment-776844df7f-r5fsb  1/1     Running   0           6h38m
buffalo-deployment-859898c6f5-zx5gj  0/1     ContainerCreating  0           8s
candidate@node-1:~$ kubectl get deploy -n gorilla
NAME            READY   UP-TO-DATE   AVAILABLE   AGE
buffalo-deployment  1/1     1             1           6h38m
candidate@node-1:~$

```

**NEW QUESTION 10**

Exhibit:



Task

Create a new deployment for running.nginx with the following parameters;

- Run the deployment in the kdpd00201 namespace. The namespace has already been created
- Name the deployment frontend and configure with 4 replicas
- Configure the pod with a container image of lfcncf/nginx:1.13.7
- Set an environment variable of NGINX PORT=8080 and also expose that port for the container above

- A. Mastered
- B. Not Mastered

Answer: A

Explanation:

Solution:

Readme Web Terminal THE LINUX FOUNDATION

```

apiVersion: apps/v1
kind: Deployment
metadata:
  creationTimestamp: null
  labels:
    app: api
  name: api
  namespace: kdpd00201
spec:
  replicas: 4
  selector:
    matchLabels:
      app: api
  strategy: {}
  template:
    metadata:
      creationTimestamp: null
      labels:
        app: api
    spec:
      containers:
      - image: lfcncf/nginx:1.13.7-alpine
        name: nginx
        resources: {}
status: {}
~
"nginx_deployment.yml" 25L, 421C 4,1 All

```

Readme Web Terminal THE LINUX FOUNDATION

```

apiVersion: apps/v1
kind: Deployment
metadata:
  labels:
    app: api
  name: api
  namespace: kdpd00201
spec:
  replicas: 4
  selector:
    matchLabels:
      app: api
  template:
    metadata:
      labels:
        app: api
    spec:
      containers:
      - image: lfcncf/nginx:1.13.7-alpine
        name: nginx
        ports:
        - containerPort: 8080
        env:
        - name: NGINX_PORT
          value: "8080"
~
23,8 All

```

Readme Web Terminal THE LINUX FOUNDATION

```

student@node-1:~$ kubectl create deployment api --image=lfcncf/nginx:1.13.7-alpine --replicas=4
-n kdpd00201 --dry-run=client -o yaml > nginx_deployment.yml
student@node-1:~$ vim nginx_deployment.yml
student@node-1:~$ kubectl create nginx_deployment.yml
Error: must specify one of -f and -k

error: unknown command "nginx_deployment.yml"
See 'kubectl create -h' for help and examples
student@node-1:~$ kubectl create -f nginx_deployment.yml
error: error validating "nginx_deployment.yml": error validating data: ValidationError(Deployment.spec.template.spec): unknown field "env" in io.k8s.api.core.v1.PodSpec; if you choose to ignore these errors, turn validation off with --validate=false
student@node-1:~$ vim nginx_deployment.yml
student@node-1:~$ kubectl create -f nginx_deployment.yml
deployment.apps/api created
student@node-1:~$ kubectl get pods -n kdpd00201
NAME                 READY   STATUS    RESTARTS   AGE
api-745677f7dc-7hnm  1/1     Running   0           13s
api-745677f7dc-9q5vp 1/1     Running   0           13s
api-745677f7dc-fd4gk 1/1     Running   0           13s
api-745677f7dc-mbnpc 1/1     Running   0           13s
student@node-1:~$

```

NEW QUESTION 10

.....

## **Thank You for Trying Our Product**

### **We offer two products:**

1st - We have Practice Tests Software with Actual Exam Questions

2nd - Questions and Answers in PDF Format

### **CKAD Practice Exam Features:**

- \* CKAD Questions and Answers Updated Frequently
- \* CKAD Practice Questions Verified by Expert Senior Certified Staff
- \* CKAD Most Realistic Questions that Guarantee you a Pass on Your First Try
- \* CKAD Practice Test Questions in Multiple Choice Formats and Updates for 1 Year

**100% Actual & Verified — Instant Download, Please Click**  
[Order The CKAD Practice Test Here](#)